

- Module Item: P20-D01V
- LED Type: DIP 546 2R1G1B
- Apply Environment : Outdoor IP65
- Pixel Pitch: Real:20mm / Virtual:10mm
- Driving Method : Static Constant Current



LED Specification	OVAL 5mm Lamp_R	OVAL 5mm Lamp_G	OVAL 5mm Lamp_B
LED Type	DIP 546	DIP 546	DIP 546
Brightness @20mA(mcd)	1000	2800	500
Wave Length (nm)	620~625	520~525	465~470
VF(V)	2.1~2.2	3.3~3.4	3.3~3.4
Viewing Angle(2θ1/2)	110/40	110/40	110/40

SPECIFICATION ITEM	DESCRIPTION
像素點距 Pixel Pitch	Real:20mm / Virtual:10mm
模組解析 Module Resolution	16x8 Pixel
像素結構 Pixel Configuration	2R/1G/1B
驅動元件 LED Driver	16 Bit
驅動方式 Driving Method	Static Constant Current
模組尺寸 Module Panel Size	320mmx160mm
環境係數 Front Module Weather Proof	IP65
模組重量 Module Panel Weight	1.25Kg
最佳視距 Option Distance	>20M
工作電壓 Working Voltage	DC +5V
最大負載 Max Working Consumption	35Watt
使用壽命 Life Time	>75,000.Hours
工作溫度 Operating Environment Temperature	-20℃~50℃
工作溼度 Operating Humidity	0~95%
單點亮度 Brightness Per Pixel	4,666mcd
模組材質 Material Of Module Frame	PC

MOQ:1000PCS

2012/01/01

## Synch LED Display Engineering CO., LTD

No.1-2, Guangfu Rd., Xitun Dist., Taichung City 407, Taiwan (R.O.C.) TEL:+886-4-24519696