


- ◆ Module Item: P25-D01
- ◆ LED Type: DIP 546 2R1G1B
- ◆ Apply Environment : Outdoor IP65
- ◆ Pixel Pitch: 25 mm
- ◆ Driving Method : Static Constant Current



| LED Specification | OVAL 5mm Lamp_R | OVAL 5mm Lamp_G | OVAL 5mm Lamp_B |
|-----------------------|-----------------|-----------------|-----------------|
| LED Type | DIP 546 | DIP 546 | DIP 546 |
| Brightness @20mA(mcd) | 1000 | 2800 | 500 |
| Wave Length (nm) | 620~625 | 520~525 | 465~470 |
| VF(V) | 2.1~2.2 | 3.3~3.4 | 3.3~3.4 |
| Viewing Angle(2θ1/2) | 110/40 | 110/40 | 110/40 |

| SPECIFICATION | ITEM | DESCRIPTION |
|---------------|-----------------------------------|-------------------------|
| 像素點距 | Pixel Pitch | 25mm |
| 模組解析 | Module Resolution | 8x8 Pixel |
| 像素結構 | Pixel Configuration | 2R/1G/1B |
| 驅動元件 | LED Driver | 16 Bit |
| 驅動方式 | Driving Method | Static Constant Current |
| 模組尺寸 | Module Panel Size | 200mmx200mm |
| 環境係數 | Front Module Weather Proof | IP65 |
| 模組重量 | Module Panel Weight | 500g |
| 最佳視距 | Option Distance | >25M |
| 工作電壓 | Working Voltage | DC +5V |
| 最大負載 | Max Working Consumption | 18Watt |
| 使用壽命 | Life Time | >75,000.Hours |
| 工作溫度 | Operating Environment Temperature | -20°C~50°C |
| 工作溼度 | Operating Humidity | 0~95% |
| 單點亮度 | Brightness Per Pixel | 4,666mcd |
| 模組材質 | Material Of Module Frame | PC |

MOQ:1000PCS

2012/01/01

Synch LED Display Engineering CO., LTD

No.1-2, Guangfu Rd., Xitun Dist., Taichung City 407, Taiwan (R.O.C.) TEL:+886-4-24519696 www.Synch.tw